

2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2818 2819 2820 2821 2822 2823 2824 2825 2826 2827 2828 2829 2830 2831 2832 2833 2834 2835 2836 2837 2838 2839 2840 2841 2842 2843 2844 2845 2846 2847 2848 2849 2850 2851 2852 2853 2854 2855 2856 2857 2858 2859 2860 2861 2862 2863 2864 2865 2866 2867 2868 2869 2870 2871 2872 2873 2874 2875 2876 2877 2878 2879 2880 2881 2882 2883 2884 2885 2886 2887 2888 2889 2890 2891 2892 2893 2894 2895 2896 2897 2898 2899 2900 2901 2902 2903 2904 2905 2906 2907 2908 2909 2910 2911 2912 2913 2914 2915 2916 2917 2918 2919 2920 2921 2922 2923 2924 2925 2926 2927 2928 2929 2930 2931 2932 2933 2934 2935 2936 2937 2938 2939 2940 2941 2942 2943 2944 2945 2946 2947 2948 2949 2950 2951 2952 2953 2954 2955 2956 2957 2958 2959 2960 2961 2962 2963 2964 2965 2966 2967 2968 2969 2970 2971 2972 2973 2974 2975 2976 2977 2978 2979 2980 2981 2982 2983 2984 2985 2986 2987 2988 2989 2990 2991 2992 2993 2994 2995 2996 2997 2998 2999 3000 3001 3002 3003 3004 3005 3006 3007 3008 3009 3010 3011 3012 3013 3014 3015 3016 3017 3018 3019 3020 3021 3022 3023 3024 3025 3026 3027 3028 3029 3030 3031 3032 3033 3

FOR UNITED STATES LETTERS PATENT

TO ALL WHOM IT MAY CONCERN:

[illegible]

CHISEL DEVICE

5

BACKGROUND OF THE INVENTION

Field of the Invention

10

The present invention relates to chisels and more particularly pertains to a new chisel device for providing a chisel and slide hammer combination.

15

Description of the Prior Art

20

The use of chisels is known in the prior art. More specifically, chisels heretofore devised and utilized are known to consist basically of familiar, expected and obvious structural configurations, notwithstanding the myriad of designs encompassed by the crowded prior art which have been developed for the fulfillment of countless objectives and requirements.

25

Known prior art includes U.S. Patent No. 5,365,648; U.S. Patent No. 5,878,822; U.S. Patent No. 2,475,041; U.S. Patent No. 2,944,521; U.S. Patent No. 1,449,136; and U.S. Des. Patent No. 346,103.

While these devices fulfill their respective, particular objectives and requirements, the aforementioned patents do not disclose a new chisel device. The inventive device includes an elongated body having a first end and a second end. An annular flange is integrally coupled to and extends around the elongated body. The flange is positioned generally between the first and second ends of the elongated body. The second end comprises a female coupler. A tubular member has an aperture extending therethrough. The elongated body extends through the aperture such that the tubular member is slidably positioned between the flange and the first end of the elongated body such that the tubular member defines a slide hammer. At least one head has a bit portion and a male coupler portion located opposite of each other. The male coupler is adapted for releasably securing to the female coupler.

In these respects, the chisel device according to the present invention substantially departs from the conventional concepts and designs of the prior art, and in so doing provides an apparatus primarily developed for the purpose of providing a chisel and slide hammer combination.

SUMMARY OF THE INVENTION

In view of the foregoing disadvantages inherent in the known types of chisels now present in the prior art, the present invention provides a new chisel device construction wherein the same can be utilized for providing a chisel and slide hammer combination.

The general purpose of the present invention, which will be described subsequently in greater detail, is to provide a new chisel device apparatus and method which has many of the advantages of

the chisels mentioned heretofore and many novel features that result in a new chisel device which is not anticipated, rendered obvious, suggested, or even implied by any of the prior art chisels, either alone or in any combination thereof.

5

To attain this, the present invention generally comprises an elongated body having a first end and a second end. An annular flange is integrally coupled to and extends around the elongated body. The flange is positioned generally between the first and second ends of the elongated body. The second end comprises a female coupler. A tubular member has an aperture extending therethrough. The elongated body extends through the aperture such that the tubular member is slidably positioned between the flange and the first end of the elongated body such that the tubular member defines a slide hammer. At least one head has a bit portion and a male coupler portion located opposite of each other. The male coupler is adapted for releasably securing to the female coupler.

There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter and which will form the subject matter of the claims appended hereto.

In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following

description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and
5 should not be regarded as limiting.

As such, those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures, methods
10 and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

Further, the purpose of the foregoing abstract is to enable the U.S. Patent and Trademark Office and the public generally, and especially the scientists, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to
15 determine quickly from a cursory inspection the nature and essence of the technical disclosure of the application. The abstract is neither intended to define the invention of the application, which is measured by the claims, nor is it intended to be limiting as to the scope of the invention in any way.

It is therefore an object of the present invention to provide a new chisel device apparatus and method which has many of the advantages of the chisels mentioned heretofore and many novel features that result in a new chisel device which is not anticipated,
25 rendered obvious, suggested, or even implied by any of the prior art chisels, either alone or in any combination thereof.
30

It is another object of the present invention to provide a new chisel device which may be easily and efficiently manufactured and marketed.

5 It is a further object of the present invention to provide a new chisel device which is of a durable and reliable construction.

10 An even further object of the present invention is to provide a new chisel device which is susceptible of a low cost of manufacture with regard to both materials and labor, and which accordingly is then susceptible of low prices of sale to the consuming public, thereby making such chisel device economically available to the buying public.

15 Still yet another object of the present invention is to provide a new chisel device which provides in the apparatuses and methods of the prior art some of the advantages thereof, while simultaneously overcoming some of the disadvantages normally associated therewith.

20 Still another object of the present invention is to provide a new chisel device for providing a chisel and slide hammer combination.

25 Yet another object of the present invention is to provide a new chisel device which includes an elongated body having a first end and a second end. An annular flange is integrally coupled to and extends around the elongated body. The flange is positioned generally between the first and second ends of the elongated body.
30 The second end comprises a female coupler. A tubular member has an aperture extending therethrough. The elongated body extends through the aperture such that the tubular member is slidably

positioned between the flange and the first end of the elongated
body such that the tubular member defines a slide hammer. At least
one head has a bit portion and a male coupler portion located
opposite of each other. The male coupler is adapted for releasably
5 securing to the female coupler.

Still yet another object of the present invention is to provide
a new chisel device that includes a slide hammer to reduce the risk
of danger of a person striking themselves with a hammer when
10 using a chisel.

Even still another object of the present invention is to
provide a new chisel device that has interchangeable bits.

These together with other objects of the invention, along with
the various features of novelty which characterize the invention,
are pointed out with particularity in the claims annexed to and
forming a part of this disclosure. For a better understanding of the
invention, its operating advantages and the specific objects attained
15 by its uses, reference should be made to the accompanying drawings
and descriptive matter in which there are illustrated preferred
embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood and objects other than
those set forth above will become apparent when consideration is
given to the following detailed description thereof. Such
description makes reference to the annexed drawings wherein:
25

Figure 1 is a schematic side view of a new chisel device
according to the present invention.
30

Figure 2 is a schematic cross-sectional view taken along line 2-2 of Figure 1 of the present invention.

5 Figure 3 is a schematic perspective view of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

10 With reference now to the drawings, and in particular to Figures 1 through 3 thereof, a new chisel device embodying the principles and concepts of the present invention and generally designated by the reference numeral 10 will be described.

15 As best illustrated in Figures 1 through 3, the chisel device 10 generally comprises an elongated body 12 having a first end 14 and a second end 16. An annular flange 18 is integrally coupled to and extends around the elongated body 12. The flange 18 is positioned generally between the first 14 and second 16 ends of the
20 elongated body 12. The elongated body 12 has a generally circular cross-section taken transversely to a longitudinal axis of the elongated body 12. The second end 16 has a threaded bore 20 extending therein which defines a female coupler.

*Sub 25
AX*

A tubular member 22 has an aperture 24 extending therethrough. The elongated body 22 extends through the aperture 24 such that the tubular member 22 is slidably positioned between the flange 18 and the first end 14 of the elongated body 22. The tubular member 22 defines a slide hammer. The tubular member 22
30 has an upper end 26, a lower end 28 and a peripheral wall 29 extending between the upper 26 and lower 28 ends. Each of a pair of annular lips 30 is attached to and extends around the peripheral

wall 29. Each of the lips 30 is positioned adjacent to one of the upper 26 and lower 28 ends of the tubular member 22.

Each of a plurality of heads 32 has a bit portion 34 and a male coupler portion 36 located opposite of each other. Each of the male coupler portions 36 comprises a threaded rod adapted for threadably coupling to the bore 20.

A first handgrip 38 is attached to and extends around the elongated body 12. The first handgrip 38 is positioned generally between the second end 16 of the elongated body 12 and the flange 18. The first handgrip 38 has a plurality of finger receiving indentations 40.

A second handgrip 42 is attached to and extends around the elongated body 12. The second handgrip 42 is positioned adjacent to and extends over the first end 14 of the elongated body 12. The second handgrip 42 has a diameter greater than diameter of the aperture 24 in the tubular member 22. The second handgrip 42 has a plurality of finger receiving indentations 44. Ideally, the handgrips 38, 42 are positioned in indentations 46 in the elongated body for better securing of the handgrips.

In use, the device 10 is used a conventional chisel however instead of using a hammer to hit the end of the chisel, the user instead slides the slide hammer 22 downward against the flange 18. The heads 32 are removable so that different bits and bit replacement can occur.

As to a further discussion of the manner of usage and operation of the present invention, the same should be apparent

from the above description. Accordingly, no further discussion relating to the manner of usage and operation will be provided.

With respect to the above description then, it is to be realized
5 that the optimum dimensional relationships for the parts of the
invention, to include variations in size, materials, shape, form,
function and manner of operation, assembly and use, are deemed
readily apparent and obvious to one skilled in the art, and all
equivalent relationships to those illustrated in the drawings and
10 described in the specification are intended to be encompassed by
the present invention.

Therefore, the foregoing is considered as illustrative only of
the principles of the invention. Further, since numerous
15 modifications and changes will readily occur to those skilled in the
art, it is not desired to limit the invention to the exact construction
and operation shown and described, and accordingly, all suitable
modifications and equivalents may be resorted to, falling within the
scope of the invention.

10006889-102601